

Shaner Promotions

2025 GUT N GO COMPACT RULES

NO PASSENGERS

NEW RULES IN RED

PARTICIPANTS REGULATIONS

Bone stock class is open to all men and women 16 and over, if under the age of 18 you must have a notarized permit signed by a parent/guardian.

Driver may move forward or backward. Driver must make contact every 60 seconds or be disqualified. No sandbagging. You must show visible damage or must move when hit.

DRIVER RULES

Drivers and passengers must be at least 18 years of age or if 16 or 17 years of age must have notarized permit by parent/guardian. Driver must furnish his/her own car. If this is a passenger heat all drivers, passengers and pit persons must sign a waiver of release of liability before entering pit area or track. IF YOU ARE NOT IN LINE TO BE CHECKED IN AT LEAST AN HOUR BEFORE START TIME YOU WILL BE CHARGED AN EXTRA \$20.00. All drivers and pit people must attend meeting prior to race time.

PREPARATION OF CARS

Front wheel drive or rear wheel drive cars no 4x4's and no pacers, wheelbase not to exceed 107 inches from center of wheel to cent of wheel (must be factory 107 inches cannot move wheels in) All glass, chrome, pot metal, head lights, taillights, back seats. Anything flammable must be removed.

THE RULES BELOW ARE THE ABSOLUTE MAX YOU MAY DO TO A CAR.

1. Dash may be removed.
2. Cars need to be 4 or 6 Cylinders only.
3. Stock gas tank can be used under car if it's in front of the rear axle. If changed to inside, it must be a metal fuel cell, no exception. Must be secured properly with no movement and no fuel leakage. No more than 6 gallons gas.
4. Battery may be relocated to inside of car but must be secured properly (1 automotive battery)
5. Hood must have a 5x5 hole cut in it to extinguish fires. Hood must open for inspection and must remain on hinges. Can be fastened one of three ways. 1) You can use 8 pieces of 3/8 chain. 6 in hood to fender, 2 from hood to bumper or 2) you can use 9 wire the same way with 3 wraps per fastening spot. Or 3) 4 spots 2x2 angle 2 inches long back to back. One welded to hood and one to the fender with one 1/2" bolt per spot and 2 spots 9 wire from hood to bumper. Must have windshield bar from top of windshield to top of fire wall you can use 9 wire, chain or 3 inch flat metal. 2 max in this area.

6. Trunks must be on hinges. You can use 8 pieces of 3/8 chain in trunk 6 to fasten trunk lid and 2 from trunk lid to bumper. Or you can use 9 wire the same way with 3 wraps per fastening spot. You can tuck 50% of trunk lid only or remove trunk lid completely.
7. BUMPERS. Must use stock factory bumper from a compact car. If it has a plastic bumper you may replace it with a 1-piece style bumper. **To mount the bumper you may weld a 4x6 flat plate to the end of the frame and bumper must bolt to the plate in 1 of 2 ways. 1) You may use (4) 1/2" bolts in the corners of the flat plate or 2) Weld a 3/4" nut on the back of the 4x6 plate and run a 3/4" bolt or all thread through the bumper into the nut.** As stated in rule 5 you can also use nine wire or chain along with bolting.
8. Doors you can use 6 pieces of 3/8 chain per door or 6 pieces of 9 wire per door with 3 wraps. Both front doors you can have a six inch wide piece of channel or equivalent from 6 inches in front of front doors to 6 inches behind front doors. May be welded or bolted. May have bar behind front seat no further back than 3 inches behind front seat.
9. TIRES: D.O.T. approved light truck tires max. **Small weld in centers are ok. No full centers or Solid wheels.**
10. **HEADER PIPES OK.**
11. REAR ENDS: Locking of rear ends permitted.
12. FRAME Notching of frame permitted but cannot be welded back together.
13. THIS IS THE MAX OF WHAT YOU CAN DO ON A BONE STOCK CAR. DO NOT DO ANYMORE THAN THIS OR YOU WON'T BE RUNNING THIS CLASS. IF YOU HAVE ANY QUESTIONS PLEASE CALL TXT Doug Huges: 217-825-9823 or Greg Matthews 217-820-5684