

2026 YOUTH GUT N GO COMPACT RULES

Participants Regulations: Bone stock class is open to all youth men and women ages 10 to 15 you must have a parent/guardian with you at sign in. must have an adult to ride passenger.

Driver may move forward or backward. Driver must make contact every 60 seconds or be disqualified. No sandbagging. You must show visible damage or must move when hit.

DRIVER RULES. Driver must furnish his/her own car. If this is a passenger heat all drivers, passengers and pit persons must sign a waiver of release of liability before entering pit area or track. IF YOU ARE NOT IN LINE TO BE CHECKED IN AT LEAST AN HOUR BEFORE START TIME YOU WILL BE CHARGED AN EXTRA \$20.00. All driver and pit people must attend meeting prior to race time.

MANDATORY PASSENGER RULES Must at least have a secure 4 point cage approved by officials for driver and passenger safety. Must have a t- handle or something similar to hold onto. Seat must be bolted down in the stock position. Must have a seat belt. Must have a sufficient amount of padding to protect the rider and passenger. If you do not have the items you will not be able to run passengers. NO EXCEPTIONS!!!!

Preparation of cars: Front wheel drive or rear wheel drive cars no 4x4's and no pacers, wheel base not to exceed 107 inches from center of wheel to center of wheel (must be factory 107 inches cannot move wheels in) All glass, chrome, pot metal, head lights, tail lights, back seats. Anything flammable must be removed. May remove dash. You must have a number on both front doors big enough to read and bright enough color to see. Also must have a number on roof sign. Use your choice of number. No profanity allowed on cars.

THESE RULES BELOW ARE THE ABSOLUTE MAX YOU MAY DO TO A CAR.

1. Cars need to be 4 or 6 Cylinders only.
2. Stock gas tank can be used under car if it's in front of the rear axle. If changed to inside it must be a metal fuel cell no exceptions. Must be secured properly with no movement and no fuel leakage. If it's hung off of the cage with a fuel tank protector it must be a minimum of 4" away from the rear seat/ speaker deck/package tray. No more than 6 gallons of gas.
3. Battery may be relocated to the inside of the car but must be secured properly (1 automotive battery)

4. Hood must have a 5x5 hole cut in it to extinguish fires. Hood must open for inspection and must remain on hinges. . Can be fastened one of three ways. 1) You can use 8 pieces of 3/8 chain. 6 in hood to fender, 2 from hood to bumper or 2) you can use 9 wire the same way with 3 wraps per fastening spot. Or 3) 4 spots 2x2 angle 2 inches long back to back. One welded to hood and one to the fender with one 1/2" bolt per spot and 2 spots 9 wire from hood to bumper Must have windshield bar from top of windshield to top of fire wall you can use 9 wire, chain or 3 inch flat metal. 2 max in this area.

5. Trunks must be on hinges. You can use 8 pieces of 3/8 chain in trunk 6 to fasten trunk lid and 2 from trunk lid to bumper. Or you can use 9 wire the same way with 3 wraps per fastening spot. You can tuck 50% of the trunk lid only or remove the trunk lid completely. No folding fender over must remain vertical. **You may beat the rear quarters in slightly and a small spot on top of fender to help achieve the trunk to roll. No pre bending of the trunk. Do not get carried away with this or you will be beating it back out.**

6. BUMPERS. Must use a stock factory bumper. If it has a plastic bumper you may replace it with a 1 piece style bumper. To mount the bumper you may weld a 4x6 flat plate to the end of the frame and bumper. The bumper must bolt to the plate in 1 of 2 ways. 1) You may use (4) 1/2" bolts in the corners of the flat plate or 2) Weld a 3/4" nut on the back of the 4x6 plate and run a 3/4" bolt or all thread through the bumper into the nut. As stated in rule 5 you can also use nine wire or chain along with bolting. **You may weld the bumper straight to frame with no added metal. Must not be welded to sub frame in any way.**

7. DOORS: You can use 6 pieces of 3/8 chain per door or 6 pieces of 9 wire per door with 3 wraps. Both front doors you can have a six inch wide piece of channel or equivalent from 6 inches in front of front doors to 6 inches behind front doors. May be welded or bolted.

8. TIRES: D.O.T. approved light truck tires max. Small weld in centers are ok. No full centers or Solid wheels.

9. HEADER PIPES OK.

10. REAR ENDS: Locking of rear ends permitted.

11. FRAME Notching of frame permitted but cannot be welded back together. **Pre ran can have 2 plates 4x4x1/4. 1 per rail**

12.CAGE: Must have a 4 point cage.The cage must be a max of 60" long and 4" away from the firewall 4" off of the floor. Must have a halo bar. Must not be more than 10" behind driver seat and straight up and down

THIS IS THE MAX OF WHAT YOU CAN DO ON A BONE STOCK CAR. DO NOT DO ANYMORE THAN THIS OR YOU WON'T BE RUNNING THIS CLASS. IF YOU HAVE ANY QUESTIONS PLEASE CALL OR TXT KIRBY. 2178213127